



Pinewood Derby Rules

Following are the inspection points

1. The car weight shall not exceed 5.0 ounces. The official race scale shall be considered final.
2. The overall length of the car shall not exceed 7 inches.
3. The overall width of the car shall not exceed 2 $\frac{3}{4}$ inches.
4. The car must have 1 $\frac{3}{4}$ " clearance between the wheels.
5. The car must have $\frac{3}{8}$ " clearance underneath the body.
6. The wood provided in the kit must be used. The block may be shaped any way that is desired.
7. The wheels supplied with the kit must be used. The wheels may not be cut, drilled, beveled or rounded. You may remove the seam from the wheels.
8. The axles supplied with the kit must be used. They may be polished or lubricated.
9. Wheel bearings, washers or bushings are prohibited.
10. The car must not ride on any type of springs.
11. The car must be freewheeling, with no starting devices.
12. No loose material of any kind, such as lead shot, may be used.

Each car must pass inspection by the official inspection committee before it will be allowed to compete. The Inspection Committee has the responsibility to disqualify those cars that do not meet these specifications

Pinewood Derby Inspection Sheet

- 1. Weight 5.0 Ounces or under..... Actual Weight _____
- 2. The overall length of the car is less than 7 inches
- 3. The overall width of the car is under 2 $\frac{3}{4}$ inches.
- 4. The car has 1 $\frac{3}{4}$ " clearance between the wheels.
- 5. The car has $\frac{3}{8}$ " clearance underneath the body.
- 6. The wood provided in the kit was used
- 7. The wheels supplied with the kit were used
- 8. The axles supplied with the kit were used
- 9. No wheel bearings, washers or bushings or springs.
- 10. No Loose material
- 11. The car is freewheeling,